

LISTING OF THE CLAIMS

A detailed listing of claims is presented below. Please amend currently amended claims as indicated below including substituting clean versions for pending claims with the same number. In addition, clean text versions of pending claims not being currently amended that are under examination are also presented. It is understood that any claim presented in a clean version below has not been changed relative to the immediate prior version.

1. (Currently Amended) A method of resource allocation comprising:

a) calculating a plurality of demand values for a plurality of components, wherein said plurality of demand values is calculated from a combination of throughput and utilization metrics;

b) predicting a plurality of response time metrics for said plurality of components based on said plurality of demand values;

c) modeling said plurality of components based on an objective function in response to said plurality of response time metrics to determine a new effective distribution of computational resources throughout said plurality of components; and

d) allocating computational resources throughout said plurality of components to reflect said new effective distribution.

2. (Original) The method as described in Claim 1, wherein said plurality of components comprise an application environment.

3. (Original) The method as described in Claim 1, wherein c) further comprises:

comparing a response time metric in said plurality of response time metrics to a service level objective; and

modeling said plurality of components when said service level objective is not satisfied.

4. (Original) The method as described in Claim 3, wherein said service level objective applies to said plurality of components on a system-wide basis.

5. (Original) The method as described in Claim 3, wherein said service level objective applies to said plurality of components on a subsystem basis.

6. (Original) The method as described in Claim 3, wherein said service level objective applies to one of said plurality of components.

7. (Original) The method as described in Claim 1, wherein a) further comprises:

receiving a plurality of metric values from said plurality of components, said plurality of metric values used to calculate said demand values.

8. (Original) The method as described in Claim 7, wherein said plurality of metric values includes throughput metrics and utilization metrics.

9. (Original) The method as described in Claim 1, wherein c) comprises:

inputting said plurality of demand values into a predictive model to determine said new effective distribution of computational resources.

10. (Original) The method as described in Claim 1, wherein d) comprises:

removing computational resources from said plurality of components.

11. (Original) The method as described in Claim 1, wherein d) comprises:

adding computational resources to said plurality of components.

12. (Currently Amended) A method of resource allocation in an application environment comprising:

- a) receiving a plurality of metric values from a plurality of components of said application environment;
- b) calculating a plurality of demand values from said plurality of metric values, wherein said plurality of demand values is calculated from a combination of throughput and utilization metrics;
- c) predicting a plurality of response time metrics for each of said plurality of components based on said plurality of demand values;
- d) modeling said plurality of components based on an objective function in response to said plurality of response time metrics to determine a new effective distribution of computational resources for said plurality of components; and
- e) allocating computational resources throughout said plurality of components to reflect said optimum number.

13. (Original) The method of resource allocation as described in Claim 12, wherein d) comprises:

modeling said plurality of components in response to said plurality of response time metrics when a service level objective is not satisfied.

14. (Original) The method of resource allocation as described in Claim 12, wherein d) further comprises:

determining a plurality of optimum numbers of computational resources, one for each of said plurality of

components, that represents said new effective distribution of computational resources.

15. (Original) The method of resource allocation as described in Claim 12, wherein e) comprises:

removing computational resources from said plurality of components.

16. (Original) The method as described in Claim 12, wherein e) comprises:

adding computational resources to said plurality of components.

17. (Original) The method as described in Claim 12, wherein c) comprises:

predicting said plurality of response time metrics using a prediction modeling technique.

18. (Original) The method as described in Claim 17, wherein said plurality of metric values includes throughput metrics and utilization metrics.

19. (Original) The method as described in Claim 12, wherein c) comprises:

inputting said plurality of demand values into a predictive model to determine said optimum number.

20. (Currently Amended) A computer system comprising:

a processor;

a computer readable memory coupled to said processor and containing program instructions that, when executed, implement a method of resource allocation comprising:

a) calculating a plurality of demand values for a plurality of components, wherein said plurality of demand values is calculated from a combination of throughput and utilization metrics;

b) predicting a plurality of response time metrics for said plurality of components based on said plurality of demand values;

c) modeling said plurality of components based on an objective function in response to said plurality of response time metrics to determine a new effective distribution of computational resources throughout said plurality of components; and

d) allocating computational resources throughout said plurality of components to reflect said new effective distribution.

21. (Original) The computer system as described in Claim 20, wherein said plurality of components comprise an application environment.

22. (Original) The computer system as described in Claim 20, wherein c) in said method of resource allocation further comprises:

comparing a response time metric in said plurality of response time metrics to a service level objective; and

modeling said plurality of components when said service level objective is not satisfied.

23. (Original) The computer system as described in Claim 22, wherein said service level objective applies to said plurality of components on a system-wide basis.

24. (Original) The computer system as described in Claim 22, wherein said service level objective applies to said plurality of components on a subsystem basis.

25. (Original) The computer system as described in Claim 22, wherein said service level objective applies to one of said plurality of components.

26. (Original) The computer system as described in Claim 20, wherein a) in said method of resource allocation further comprises:

receiving a plurality of metric values from said plurality of components, said plurality of metric values used to calculate said demand values.

27. (Original) The computer system as described in Claim 26, wherein said plurality of metric values includes throughput metrics and utilization metrics.

28. (Original) The computer system as described in Claim 20, wherein c) in said method of resource allocation comprises:

inputting said plurality of demand values into a predictive model to determine said new effective distribution of computational resources.

29. (Original) The computer system as described in Claim 20, wherein d) in said method of resource allocation comprises:

removing computational resources from said plurality of components.

30. (Original) The computer system as described in Claim 20, wherein d) in said method of resource allocation comprises:

adding computational resources to said plurality of components.

31. (Currently Amended) A communication network comprising:

a plurality of computational resources;

an application environment having a plurality of network nodes coupled together;

a plurality of components in said application environment servicing an application, each of said plurality of components including at least one computational resource from said plurality of computational resources, each of said plurality of components residing on one of said plurality of network nodes;

a plurality of metrics measured at each of said plurality of components for calculating a plurality of demand values, wherein said plurality of demand values is calculated from a combination of throughput and utilization metrics;

a functional objective for defining an optimum number of computational resources in said application environment; and

a dynamic resource manager coupled to said application environment for determining a new effective distribution of computational resources throughout each of said plurality of components in response to said plurality of demand values in order to satisfy said functional objective.

32. (Original) The communication network as described in Claim 31, wherein said plurality of metrics comprises throughput metrics and utilization metrics.

33. (Original) The communication network as described in Claim 31, further comprising:

a prediction model for predicting a plurality of response time metrics for said plurality of components based on said plurality of demand values; and

a mathematical model for modeling said plurality of components in response to said plurality of response time metrics for determining said new effective distribution of computational resources.

34. (Original) The communication network as described in Claim 31, further comprising:

a plurality of component managers, one for each of said plurality of components, for managing the addition and removal of computational resources in said plurality of components in response to notices from said dynamic resource manager.

35. (Original) The communication network as described in Claim 31, wherein said plurality of components comprise a local area network (LAN).